



- Designed for and validated with Intel Server boards
- Option for two 5.25" and one 3.5" peripherals
- One 450W power supply, two system fans, up to 6 fixed-drive bays
- Option for 5 hot-swap SCSI or 5 hot-swap SATA drive(03)
- Compliance with Blue Angel acoustic requirements(<=48dBA idle, <=55dBA at maximum speed)
- Compliance with international safety and EMC regulatory approvals

Case Size	5.3U Pedestal
Main Board Size	CEB 12*10 / ATX 12*9.6 / 12*13
HDD Bays	6 IDE HDD drive bays or option 8721 SCSI drive module
Drive Bays	1x3.5"drive bay 2 x 5.25"drive bay 6 x IDE drive bays EN-8711SCSI drive module(optional)
Expansion Slot	7 x PCI slots
Cooling Fan	1 x 120mm rear fan & optional 1 x 90mm HDD fan
LED Indicators	1 x PSU/Sleep, 1 x NIC, 1 x NIC2, 1 x HDD, 1 x Status
I/O Port	Standard ATX I/O
Power Supply	600W
Dimensions	452.8 x 235.2 x 447mm
Weight	11.32kg (case only) 13kgs (case + power supply)
Security	1xMechanical Lock(front bezel) 1xIntrusion Detector(rear panel)
Support	Nocona, AMD and CEB , P4 Prescott server