



17"

Active
screen size

8 ms

Very low response
time for fast image
formation



Integrated
speakers

Belinea 10 17 15

The true office standard

The Belinea 10 17 15 is presented here with an even shorter response time. Just as before, the monitor stands out with trusted, reliable technical features and all this at a low price.

The response time of the models is now just 8 milliseconds and thus able to meet the demands for increasingly fast panels. This is what makes the Belinea 10 17 15, with its integrated speakers, an ideal multimedia display. The other technical data provides yet more evidence that the display offers above average value for money. With a contrast ratio of 500:1, a viewing angle of 140° horizontal and 125° vertical and a brightness value of 270 cd/m², the Belinea 10 17 15 shows off its popular, solid characteristics and is a recommendable entry-level monitor in the 17-inch range.

Key features:

- 17-inch (43.18 cm) with TN panel
- 8 ms response time
- Contrast ratio 500:1
- Integrated speakers
- SilverBlackStyle

Application areas:

- Multimedia industry
- Small and medium business
- Attractively-priced design model for prestigious workplaces





Belinea 10 17 15 Art. No. 11 17 46

Technical data

Panel characteristics

Screen size	17"
Screen size in inches (visible)	17
Screen size in cm (visible)	43.18
Maximum picture size (W x H) in mm	338 x 270
Physical resolution	1.3 Mega Pixel (1280 x 1024)
Dot pitch (H x V) in mm	0.264 x 0.264
Panel technology	TN
Presentable colours	16.2 million
Brightness in cd/m ² (typ.)	270
Contrast ratio (typ.)	500:1
Viewing angle, h/v (CR > 5:1)	160° / 145°
Viewing angle, h/v (CR > 10:1)	140° / 125°
Response time in ms:	8

Electrical data

Horizontal frequency in kHz	31-83
Vertical frequency in Hz	56-75
Max. bandwidth (dot rate) in MHz	135
Input voltage 100-240V, 50-60 Hz	•
Max. power consumption in watts (on/sleep)	45 / 4

Features

Speakers	2 x 1 watt
Height adjustable in mm	–
Rotatable through 90°	–
Power supply internal / external	• / –
Tilt angle, forwards / backwards	22° / 5°
Swivel-mounted to right / left	– / –
Colour	ClassicGrey

OSD / Settings options

Brightness / contrast	• / •
Clock / phase	• / •
Image position (horizontal / vertical)	• / •
Auto-Setup / Reset	• / •
Colour temp. (5500K, 6500K, 9300K, User, SRGB)	– / • / • / • / •
Display at low resolution: Full image / 1:1	• / –
Frequency display / video signal switching	• / –
Volume	•

Monitor controls

-AutoSetup / brightness / contrast	• / • / •
-Volume / menu / power	Mute / • / •

Max. image refresh rates in Hz for resolution analogue / digital

640 x 480	75 / –
800 x 600	75 / –
1024 x 768	75 / –
1152 x 864	75 / –
1280 x 1024	75 / –
1600 x 1200	– / –

Test certificates / Standards

Plug & Play:	
-DDC 2B / DDC-CI	• / •
Ergonomics:	
-TÜV Ergo (ISO 13406-II) / TCO99 / TCO03	• / • / –
Safety:	
-TÜV GS / CE	• / •
Power Management:	
-Energy Star / Energy Label / TCO99 / TCO03	• / – / • / –
MAC compliant	•
Anti-theft device:	
-Kensington Lock compliant	•
VESA Mounting compliant (hole spacing in mm)	100 x 100

Connections

Analogue: D-SUB 15 pin mini	•
Digital: DVI-D (24-pin)	–
Headphone connection / Audio input	– / •
USB (1 up/3 down)	–

Accessories

Manual (CD / Print)	• / –
Power cable (1.8 m)	•
Video cable D-Sub 15 pin mini (1.8 m)	•
DVI-D cable, 1.8 m (optional)	–
Audio cable (1.8 m) / USB cable	• / –
Pivot Software (optional)	–

Dimensions

Size (W x H x D) in mm	380 x 401 x 214
Size (W x H x D) in mm without stand	380 x 344 x 57
Net / gross weight in kg	3.7 / 5.45

Service

3 years swap out warranty incl. panel and backlight	•
---	---

Belinea is the monitor brand of MAXDATA.

With compliments:

